Product Datasheet



EMBLEM TREND Champion Micro Vinyl II

TREND Champion Micro Vinyl II

Matchcode: SFOMPO-XI

Material: Vinyl, selfadhesive, monomeric

Finish: microporous matt

Color: white

Weight/Thickness: 135my, film and glue

Liner: double-sided siliconised

Paper, 140g/m²

Glue: polyacrylate dispersion

Tackiness: 7N/25mm (A.F.E.R.A.)

Laminating: cold, solvent glue preferred

Bonding: $>15^{\circ}C$

Flame Retardant: no

Width of Rolls: 36" / 42" / 50" / 54" / 60"

Length of Rolls: 20m

BubbleJet Dye: yes (laminating required)

BubbleJet Pigment: yes

Piezo Dye: yes (laminating required)

Piezo pigment: yes Piezo Oil: yes Piezo Eco Solvent: yes Piezo Solvent: no

Compatible Printers:

HP 2XXX, 3XXX 5XXX dye and pigment Encad NovaJet dye and pigment Roland FJ dye and pigment Roland SC, SJ and SP ECO-Solvent Mutoh RJ dye and pigment Mutoh RH ECO-Solvent Mimaki JV dye and pigment Seiko IP4500 oil

Description:

EMBLEM SFOMPO-XI is a white, matt, self-adhesive vinylfilm to be printed with waterbased dye- and pigmented inks, oilbased inks and ECO-solvent inks. The film is coated with a microporous inkjet-coating.

All inks, apart from dyebased inks, are achieving water-resistant prints. We advice the user to laminate every print for outside use, to protect it from abrasion. Prints which have produced with pigmented inks are smear- and water-resistant up to one year.

Every print which has been produced with dyebased inks has to laminated to protect it against oxidation.

It is possible to laminate SFOMPO-XI without edge-protection by using EMBLEM lamination films with solvent glue. Professional handling eliminates the risk of intruding of water by the edges for more than 3-5mm.

Before lamination the print has to be complete dryed, otherwise there is a risk of lumps.

The use of high ink-limits may cause clouding. High ink-quantity may also cause a longer dryingtime.

To avoid a mess of unprinted areas with ink it is advisable to swill the the print with clear water to remove excess ink.

For the preventation of fingerprints it is advisable to use cotton gloves.

Because of the great number of potential influences at object time and applinace of the above-mentioned materials, on which we have no bearing, test prints have to be effected by the user himself. A legally binding warranty can not be deduced from our specifications. Every liability and warranty that goes beyond the warranty of the product amounting to the product's value as well as entitlements to damages are excluded.